

FROST

Fighters

PORTABLE HEATERS



INDIRECT FIRED



DIRECT FIRED

Temporary Heating Equipment Since 1965

Clean, Safe, Reliable Portable Heat – wherever you need it – indoors or out!

FROST

Fighters

IS PERFORMANCE



**INDUSTRIAL
COMMERCIAL
EQUIPMENT
MANUFACTURING LTD.**

685 Berry Street
Winnipeg, MB R3H 0S4
Toll Free: 1-888-792-0374
Direct: (204) 775-8252
Fax: (204) 783-6794
Website: www.frost-fighters.com
Corporate: www.ice-ww.com

INDIRECT FIRED

OIL

Model	OHV 200 - OIL	OHV 350 - OIL	OHV 500 - OIL	OHV 600 - OIL
Capacity	210,000 BTU	320,000 BTU	420,000 BTU	505,000 BTU
Heated Air	2,500 CFM	2,500 CFM	3,100 CFM	3,100 CFM
Discharge Temp. *	150°F	200°F	180°F	220°F
Weight	405 lbs	467 lbs	467 lbs	467 lbs
Approved	ETL	CSA	CSA	ETL
Shipping Dimensions				
Crated (LxWxH)	83" x 37.5" x 52.5"	83" x 37.5" x 52.5"	83" x 37.5" x 52.5"	83" x 37.5" x 52.5"

PROPANE / NATURAL GAS

Model	OHV 200 - LP/NG	OHV 350 - LP/NG	OHV 500 - LP/NG
Capacity	210,000 BTU	350,000 BTU	450,000 BTU
Heated Air	2,500 CFM	2,500 CFM	3,100 CFM
Discharge Temp. *	150°F	200°F	210°F
Weight	405 lbs	455 lbs	455 lbs
Approved	ETL	CSA	ETL
Shipping Dimensions			
Crated (LxWxH)	83" x 37.5" x 52.5"	83" x 37.5" x 52.5"	83" x 37.5" x 52.5"

*Discharge Temp. (@50°F ambient)

DIRECT FIRED

Model	DF400	DF1000	DF1500
Capacity	400,000 BTU	1,000,000 BTU	1,500,000 BTU/HI FIRE 800,000 BTU/LOW FIRE
Fuel	Vapor Propane/Natural Gas	Vapor Propane/Natural Gas	Vapor Propane/Natural Gas
Manifold Pressure	Propane 1.1"w.c. Natural Gas 2.8"w.c.	Propane 2.4"w.c. Natural Gas 6.0"w.c.	Propane 3.2"w.c. Natural Gas 7.8"w.c.
Gas Consumption	157 CFH/LP 4.35 US Gal/HR 390 CFH/NG 10.7 US Gal/HR	393 CFH/10.9 US Gal/HR-LP 974 CFH/27.2 US Gal/HR-NG	589 CFH/16.5 US Gal/HR-LP 1461 CFH/40.8 US Gal/HR-NG
Gas Consumption	3/4" NPT	1.25" NPT	1.25" NPT
Electrical Requirements	120 Volts 15 Amps Circuit	120 Volts 20 Amp Circuit	120 Volts 20 Amp Circuit
Fan	2500 CFM 1/2 HP, 16" Diameter	7700 CFM 1 HP, 24" Diameter	7700 CFM 1 HP, 24" Diameter
Shipping Dimensions			
Crated (LxWxH)	51" x 30.5" x 33"	74.5" x 39.5" x 52.5"	74.25" x 39.5" x 52.5"
Weight	206 lbs	415 lbs	415 lbs
Approved	ETL	ETL	ETL

Temporary Heating Equipment Since 1965